

Belt conveyors are used for the transport of coarse and fine matter such as screenings, dewatered sludge and various solid materials. They can be installed horizontally or inclined to suit application requirements. Belt conveyors are tailored to the particular application to serve system requirements taking into consideration the material to be conveyed.

CONVEYOR BELTS



Disclaimer: The information contained on this data sheet is intended for general information only and should not be considered to be complete or definitive. S.K. Euromarket Ltd reserves the right to make changes at any time, without notice, to any element of the equipment presented.

AREAS OF APPLICATION

- Water Treatment
- Sewage treatment
- Industrial effluent treatment
- Solid treatment

KEY FEATURES

- Tailor made design
- Robust construction
- Variable length and speed
- Adjustable belt tension
- Totally enclosed horizontal or inclined rollers
- Washing system maybe integrated
- Adjustable support legs
- Replaceable belt

TECHNICAL INFORMATION

BELT WIDTH	40mm, 60mm, 80mm, other on request
BELT LENGTH	Variable
ROTATIONAL SPEED CONTROL	Variable mechanical or electronic (optional)
CONSTRUCTION MATERIAL	Stainless steel AISI304 or AISI316



For further details please request the technical specifications and drawings

euromarket
Solution providers for all your needs

S.K. EUROMARKET LTD
Water & Wastewater Engineering
 44, Spyrou Kyprianou Street
 3rd Limassol Industrial Estate (Ipsonas)
 P.O. Box 56550, 3308 Limassol, Cyprus
 Tel. : +357 25568880, Fax : +357 25572518
 info@euromarket-cy.com
 www.euromarket-cy.com



Distributed by: